

Double Row Terminal Blocks

Kulka® 600 GP Series

300 Volts AC/DC (Class B)

150 Volts AC/DC (Class C)

Class D does not apply



600 GP 07 PSB

Specifications:

- Base, Phenolic, 150°C
- Open Back Design (Insulator Strip required for Voltage Rating - see page 108)
- JJ (GDI-30F) Material Available
- Screws, #5-40 Binder Head, Phil-Slot, Brass
- Terminals, Plated Brass
- 1-22 Poles
- 3/8" Centers
- Wire Range With Wire Binding Screw
#12 - #22 AWG – 15 Amps
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

| Kulka® Catalog # | # of poles | Dimensions | |
|---------------------|------------|------------|------|
| | | A | B |
| 600 GP 01 PSB | 1 | 1.03 | 0.75 |
| 600 GP 02 PSB | 2 | 1.41 | 1.13 |
| 600 GP 03 PSB | 3 | 1.78 | 1.50 |
| 600 GP 04 PSB | 4 | 2.16 | 1.88 |
| 600 GP 05 PSB | 5 | 2.53 | 2.25 |
| 600 GP 06 PSB | 6 | 2.91 | 2.63 |
| 600 GP 07 PSB | 7 | 3.28 | 3.00 |
| 600 GP 08 PSB | 8 | 3.66 | 3.38 |
| 600 GP 09 PSB | 9 | 4.03 | 3.75 |
| 600 GP 10 PSB | 10 | 4.41 | 4.13 |
| 600 GP 11 PSB | 11 | 4.78 | 4.50 |
| 600 GP 12 PSB | 12 | 5.16 | 4.88 |
| 600 GP 13 PSB | 13 | 5.53 | 5.25 |
| 600 GP 14 PSB | 14 | 5.91 | 5.63 |
| 600 GP 15 PSB | 15 | 6.28 | 6.00 |
| 600 GP 16 PSB | 16 | 6.66 | 6.38 |
| 600 GP 17 PSB | 17 | 7.03 | 6.75 |
| 600 GP 18 PSB | 18 | 7.41 | 7.13 |
| 600 GP 19 PSB | 19 | 7.78 | 7.50 |
| 600 GP 20 PSB | 20 | 8.16 | 7.88 |
| 600 GP 21 PSB | 21 | 8.53 | 8.25 |
| 600 GP 22 PSB | 22 | 8.91 | 8.63 |

mm=dim X 25.4

Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

| CATALOG # | PRODUCT DESCRIPTION | PAGE REFERENCE |
|-----------|-------------------------------|----------------|
| MSP | | |
| KULKA | | |
| KT19 | Full Quick Connect (0° Flat) | See Page 101 |
| KT20 | Full Quick Connect (45° Bend) | See Page 101 |
| KT21 | Full Quick Connect (90° Bend) | See Page 101 |
| KT25 | Half Quick Connect (0° Flat) | See Page 101 |
| KT26 | Half Quick Connect (45° Bend) | See Page 101 |
| KT27 | Half Quick Connect (90° Bend) | See Page 101 |
| ST | Full Solder | See Page 102 |
| 3/4 ST | Half Solder | See Page 102 |
| Y | Feed Thru Solder (.312) | See Page 102 |
| YSY | Feed Thru Solder (.500) | See Page 102 |
| Z | Lug Over the Side (.625) | See Page 102 |
| J 600 | Line to Line Jumper | See Page 103 |
| 600 RJ(S) | Multiple Position Jumper | See Page 103 |
| 2004 | Feed Thru Solder | See Page 105 |

Quick Connects: .020" x .187"

See pages 100-111 for terminal block accessories

