

# Double Row Terminal Blocks

## Kulka® 600A/800A GP Series

300 Volts AC/DC (Class B)

150 Volts AC/DC (Class C)

Class D does not apply



600A GP 06

### Specifications:

- Base, Phenolic, 150°C
- Open Back Design (Insulator Strip required for Voltage Rating - see page 108)
- JJ (GDI-30F) Material Available
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-22 Poles
- 3/8" Centers
- Wire Range With Wire Binding Screw  
#12 - #22 AWG – 15 Amps
- 800A Series (Riveted KT's) - see page 98
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

Double Row Terminal Blocks

Kulka® Catalog #	# of poles	Dimensions	
		A	B
600A GP 01	1	1.03	0.75
600A GP 02	2	1.41	1.13
600A GP 03	3	1.78	1.50
600A GP 04	4	2.16	1.88
600A GP 05	5	2.53	2.25
600A GP 06	6	2.91	2.63
600A GP 07	7	3.28	3.00
600A GP 08	8	3.66	3.38
600A GP 09	9	4.03	3.75
600A GP 10	10	4.41	4.13
600A GP 11	11	4.78	4.50
600A GP 12	12	5.16	4.88
600A GP 13	13	5.53	5.25
600A GP 14	14	5.91	5.63
600A GP 15	15	6.28	6.00
600A GP 16	16	6.66	6.38
600A GP 17	17	7.03	6.75
600A GP 18	18	7.41	7.13
600A GP 19	19	7.78	7.50
600A GP 20	20	8.16	7.88
600A GP 21	21	8.53	8.25
600A GP 22	22	8.91	8.63

mm=dim X 25.4

### Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

CATALOG #	PRODUCT DESCRIPTION	PAGE REFERENCE
MSP	Full Solder	See Page 102
KULKA	Half Solder	See Page 102
KT19	Full Quick Connect (0° Flat)	See Page 101
KT20	Full Quick Connect (45° Bend)	See Page 101
KT21	Full Quick Connect (90° Bend)	See Page 101
KT25	Half Quick Connect (0° Flat)	See Page 101
KT26	Half Quick Connect (45° Bend)	See Page 101
KT27	Half Quick Connect (90° Bend)	See Page 101
ST	Full Solder	See Page 102
3/4 ST	Half Solder	See Page 102
Y	Feed Thru Solder (.312)	See Page 102
YSY	Feed Thru Solder (.500)	See Page 102
Z	Lug Over the Side (.625)	See Page 102
J 600	Line to Line Jumper	See Page 103
600 RJ(S)	Multiple Position Jumper	See Page 103
3860	Wire Clamp Screw, Brass	See Page 103
3865	Wire Clamp Screw	See Page 103
2002	Stud	See Page 105
PSB	Phil-Slot Brass Screw	Consult C/S

Quick Connects: .020" x .187"

See pages 100-111 for terminal block accessories

