

# Double Row Terminal Blocks

## Kulka® 601/801 GP Series

### 300 Volts AC/DC (Classes B/C)

*Class D does not apply*



601 GP 06

#### Specifications:

- Base, General Purpose Phenolic, 150°C
- Open Back Design (Insulator Strip required for Voltage Rating - see page 108)
- JJ (GDI-30F) Material Available
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-23 Poles
- 7/16" Centers
- Wire Range With Wire Binding Screw #12 - #22 AWG – 20 Amps
- 801 Series (Riveted KT's) - see page 98
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

Kulka® Catalog #	# of poles	Dimensions	
		A	B
601 GP 01	1	1.19	0.88
601 GP 02	2	1.62	1.31
601 GP 03	3	2.06	1.75
601 GP 04	4	2.50	2.19
601 GP 05	5	2.94	2.63
601 GP 06	6	3.37	3.06
601 GP 07	7	3.81	3.50
601 GP 08	8	4.25	3.94
601 GP 09	9	4.69	4.38
601 GP 10	10	5.12	4.81
601 GP 11	11	5.56	5.25
601 GP 12	12	6.00	5.69
601 GP 13	13	6.44	6.13
601 GP 14	14	6.87	6.56
601 GP 15	15	7.31	7.00
601 GP 16	16	7.75	7.44
601 GP 17	17	8.19	7.88
601 GP 18	18	8.62	8.31
601 GP 19	19	9.06	8.75
601 GP 20	20	9.50	9.19
601 GP 21	21	9.94	9.63
601 GP 22	22	10.37	10.06
601 GP 23	23	10.81	10.50

mm=dim X 25.4

#### Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

CATALOG #	PRODUCT DESCRIPTION	PAGE REFERENCE
MSP		
KULKA		
KT37	Full Quick Connect (0° Flat)	See Page 101
KT38	Full Quick Connect (45° Bend)	See Page 101
KT39	Full Quick Connect (90° Bend)	See Page 101
KT43	Half Quick Connect (0° Flat)	See Page 101
KT44	Half Quick Connect (45° Bend)	See Page 101
KT45	Half Quick Connect (90° Bend)	See Page 101
ST	Full Solder	See Page 102
3/4 ST	Half Solder	See Page 102
Y	Feed Thru Solder (.422)	See Page 102
YSY	Feed Thru Solder (.687)	See Page 102
J 601	Line to Line Jumper	See Page 103
601 RJ(S)	Multiple Position Jumper	See Page 103
3765	Wire Clamp Screw	See Page 103
3760	Wire Clamp Screw	See Page 103
2102	Stud	See Page 105
2104	Feed Thru Solder	See Page 105
2108	Individual Screw Terminals	See Page 105
PSB	Phil-Slot Brass Screw	Consult C/S

Quick Connects: .032" x .250"

See pages 100-111 for terminal block accessories

