

Double Row Terminal Blocks

670A RZ Series

300 Volts AC/DC (Class B)

150 Volts AC/DC (Class C)

Class D does not apply



670A RZ 06

Specifications:

- Base, Thermoplastic, 130°C (U.L. RTI)
- Closed Back Design
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-30 Poles
- 3/8" Centers
- Wire Range With Wire Binding Screw
#12 - #22 AWG – 20 Amps
- Wire Range With Sems Pressure Screw #14 - #22 AWG
Stranded or Solid Wire - 15 Amps
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

| MSP Catalog # | # of poles | Dimensions | |
|------------------|------------|------------|-------|
| | | A | B |
| 670A RZ 01 | 1 | 1.03 | 0.75 |
| 670A RZ 02 | 2 | 1.41 | 1.13 |
| 670A RZ 03 | 3 | 1.78 | 1.50 |
| 670A RZ 04 | 4 | 2.16 | 1.88 |
| 670A RZ 05 | 5 | 2.53 | 2.25 |
| 670A RZ 06 | 6 | 2.91 | 2.63 |
| 670A RZ 07 | 7 | 3.28 | 3.00 |
| 670A RZ 08 | 8 | 3.66 | 3.38 |
| 670A RZ 09 | 9 | 4.03 | 3.75 |
| 670A RZ 10 | 10 | 4.41 | 4.13 |
| 670A RZ 11 | 11 | 4.78 | 4.50 |
| 670A RZ 12 | 12 | 5.16 | 4.88 |
| 670A RZ 13 | 13 | 5.53 | 5.25 |
| 670A RZ 14 | 14 | 5.91 | 5.63 |
| 670A RZ 15 | 15 | 6.28 | 6.00 |
| 670A RZ 16 | 16 | 6.66 | 6.38 |
| 670A RZ 17 | 17 | 7.03 | 6.75 |
| 670A RZ 18 | 18 | 7.41 | 7.13 |
| 670A RZ 19 | 19 | 7.78 | 7.50 |
| 670A RZ 20 | 20 | 8.16 | 7.88 |
| 670A RZ 21 | 21 | 8.53 | 8.25 |
| 670A RZ 22 | 22 | 8.91 | 8.63 |
| 670A RZ 23 | 23 | 9.28 | 9.00 |
| 670A RZ 24 | 24 | 9.66 | 9.38 |
| 670A RZ 25 | 25 | 10.03 | 9.75 |
| 670A RZ 26 | 26 | 10.41 | 10.13 |
| 670A RZ 27 | 27 | 10.78 | 10.50 |
| 670A RZ 28 | 28 | 11.16 | 10.88 |
| 670A RZ 29 | 29 | 11.53 | 11.25 |
| 670A RZ 30 | 30 | 11.91 | 11.63 |

mm=dim X 25.4

Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

| CATALOG # MSP | KULKA PRODUCT DESCRIPTION | PAGE REFERENCE |
|------------------|------------------------------------|-------------------|
| | KT19 Full Quick Connect (0° Flat) | See page 101 |
| | KT20 Full Quick Connect (45° Bend) | See page 101 |
| | KT21 Full Quick Connect (90° Bend) | See page 101 |
| | KT25 Half Quick Connect (0° Flat) | See page 101 |
| | KT26 Half Quick Connect (45° Bend) | See page 101 |
| | KT27 Half Quick Connect (90° Bend) | See page 101 |
| | ST Full Solder | See page 102 |
| | 3/4 ST Half Solder | See page 102 |
| L | Y Feed Thru Solder (.312) | See page 102 |
| | J 600 Line to Line Jumper | See page 103 |
| | 600RJ(S) Multiple Position Jumper | See page 103 |
| | 3865 Sems Pressure Saddle Screw | See page 103 |
| PSB | Phil-Slot Brass Screw | Consult C/S |

Quick Connects: .020" x .187"

See pages 100-111 for terminal block accessories

