

Studded Power Feed Thru Terminal Blocks

Specifications:

Electrical:

- 300 Volts AC/DC (UL 1059 Class B and C)
- 175 Amps
- Wire Range 2/0 - #8
- Accommodates Two Hole Compression Lugs on .625" Centers – wires #2 and larger may require narrow lugs

General/Mechanical:

- Base, Thermoplastic, 125°C (UL RTI)
- Studs, Brass, Nickel Plated
- 2 – 6 Poles
- .73" Centers
- Application Torque: 35 lbf-in for #10 - 32 and M5.
50 lbf-in for 1/4" - 20 and M6
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant



ST722B2502

Catalog Number	Number of Poles	Dimensions A	
		Inches	Metric
ST722BXX02	2	1.55	(39.37)
ST722BXX03	3	2.28	(57.91)
ST722BXX04	4	3.01	(75.45)
ST722BXX05	5	3.74	(95.00)
ST722BXX06	6	4.47	(113.54)

Replace XX with thread size: 19 - #10-32 Stud
25 - 1/4" - 20 Stud
M5 - M5 Stud
M6 - M6 Stud

See page 57 for available covers

LENGTH	"P"	
	ENG.	MET.
1-LINE	.62	15.7
2-LINE	1.35	34.3
3-LINE	2.08	52.8
4-LINE	2.81	71.4
5-LINE	3.54	89.9
6-LINE	4.27	108.5

