



# MOTORTRONICS™

*Solid State AC Motor Controls*



## *Current* **TRANSFORMERS**

**600V Ansi Rated Window Type**



### **Features:**

Voltage: 600V Ansi Rated Window Type  
Application: Relaying and Metering  
Frequency: 50 - 400 Hz  
Insulation Level: 600 Volts, 10 kV BIL full wave

# Current TRANSFORMERS

600V Current Transformers ANSI Rated Window Type

Frequency: 50 - 400 Hz

Insulation Level: 600 Volts, 10 kV BIL full wave

<b>MODEL 8</b>	Window Sizes 3.25"	Current Ratio Range: 200:5 ~ 4000:5
<b>MODEL 10</b>	Window Sizes 1.56"	Current Ratio Range: 50:5 ~ 600:5
<b>MODEL 19</b>	Window Sizes 4.25"	Current Ratio Range: 300:5 ~ 3000:5
<b>MODEL 21</b>	Window Sizes 1.25", 1.63" 2.00", 2.50" 3.13"	Current Ratio Range: 50:5 ~ 1000:5
<b>MODEL 64</b>	Window Sizes 1.56", 2.00" 2.50"	Current Ratio Range: 50:5 ~ 500:5
<b>MODEL 100</b>	Window Sizes 4.00"	Current Ratio Range: 200:5 ~ 3000:5
<b>MODEL 110</b>	Window Sizes 2.06"	Current Ratio Range: 200:5 ~ 3000:5
<b>MODEL 112-117</b>	Window Sizes 2.25", 2.75" 3.25", 4.00" 4.62"	Current Ratio Range: 50:5 ~ 1200:5
<b>MODEL 115MR</b>	Window Sizes 4.00"	Current Ratio Range: 50:5 ~ 2000:5
<b>MODEL 117MR</b>	Window Sizes 4.62"	Current Ratio Range: 50:5 ~ 2000:5
<b>MODEL 120</b>	Window Sizes 5.75"	Current Ratio Range: 200:5 ~ 4000:5
<b>MODEL 125</b>	Window Sizes 6.31"	Current Ratio Range: 600:5 ~ 4000:5
<b>MODEL 126</b>	Window Sizes 8.25"	Current Ratio Range: 400:5 ~ 5000:5
<b>MODEL 130</b>	Window Sizes 5.75"	Current Ratio Range: 200:5 ~ 4000:5
<b>MODEL 135 / 135MR</b>	Window Sizes 5.75"	Current Ratio Range: 50:5 ~ 5000:5



P/N: CT-A-600V102209

CORPORATE HEADQUARTERS

CTi Automation - Phone: 800.894.0412 - Fax: 208.368.0415 - Web: [www.ctiautomation.net](http://www.ctiautomation.net) - Email: [info@ctiautomation.net](mailto:info@ctiautomation.net)