



MOTORTRONICS™
Solid State AC Motor Controls


LOW VOLTAGE TRANSFORMERS

600V Class
Ansi Rated

LOW VOLTAGE TRANSFORMERS

INDOOR VOLTAGE TRANSFORMERS

600V Class 




MODEL 467 : SINGLE PHASE

Accuracy Class: + 1% at all burdens up to 5VA at 1.0 and 0.95 P.F.

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 40 VA at 30°C amb. / 27 VA at 55°C amb.




MODEL 468 : SINGLE PHASE

Accuracy Class: + 0.6% at all burdens up to 7.5VA and + 1.5% with 20VA burden

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 75 VA at 30°C amb. / 50 VA at 55°C amb.




MODEL 460 : SINGLE PHASE

Accuracy Class: 0.6 W. 1.2 x 60 Hz.

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 150 VA at 30°C amb. / 100 VA at 55°C amb.




MODEL 450 : SINGLE PHASE

Accuracy Class: 0.3 W, X, M & Y 1.2Z@ 0.3 W, 0.6 X, M & Y

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 750 VA at 30°C amb. / 500 VA at 55°C amb.



MODEL 475 : SINGLE PHASE

Accuracy Class: 0.3 W. 0.6 x, 1.2 M at 60 Hz.

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 300 VA at 30°C amb. / 200 VA at 55°C amb.




MODEL 2VT469 : THREE PHASE

Accuracy Class: + 1% at all burdens up to 5 VA at 1.0 and 0.95 P.F.

Available Primary Voltage Ratios: 69.3V, 120V, 208V, 240V, 277V, 288V, 300V, 346V, 480V, 600V to 120V

Thermal Rating: 40 VA at 30°C amb. / 27 VA at 55°C amb.



MODEL 3VTN460 : THREE PHASE LINE TO NEUTRAL / 3VTL460 : THREE PHASE LINE TO LINE

Accuracy Class: 0.6 W, 1.2 X at 60 Hz.

Available Primary Voltage Ratios 3VTN460 Line to Neutral: 120V, 208V, 240V, 288V, 480V, 600V to 120V

Available Primary Voltage Ratios 3VTL460 Line to Line: 120V, 208V, 240V, 288V, 480V, 600V to 120V

Thermal Rating: 150 VA at 30°C amb. / 100 VA at 55°C amb.

Transformer Insulation Level: 600 Volts, 10 kV BIL full wave



P/N: VT-600V122909

CORPORATE HEADQUARTERS

CTi Automation - Phone: 800.894.0412 - Fax: 208.368.0415 - Web: www.ctiautomation.net - Email: info@ctiautomation.net